

MANSIL[®]-190/190G

**RUBBER GRADE PRECIPITATED SILICA
(SPRAY DRIED POWDER / GRANULES)**

DESCRIPTION

ULTRA HIGH SURFACE AREA, ULTRA WHITE SPRAY DRIED POWDER OR GRANULES
HAVING EXCELLENT DISPERSION PROPERTIES RESULTING IN DESIRED
REINFORCEMENT IN RUBBER COMPOUND.

SPECIFICATIONS

Sr. No.	PHYSICO-CHEMICAL PROPERTIES	UNIT	TEST METHOD	MANSIL-190	MANSIL-190G
1	Appearance	**	Visual	White Spray Dried Powder	White Granules
2	Bulk Density (When packed)	gms/lit.	ISO 787/11	250 ± 30	330 ± 30
3	Moisture (at 105°C/2 hrs.)	%	ISO 787/2	6.0 Max	6.0 Max
4	Ignition Loss (at 1000°C/2 hrs.) on anhydrous basis	%	ISO 3262/11	6.0 Max	6.0 Max
5	pH (5% aqu. suspn.)	**	ISO 787/9	6.0 - 7.0	6.0 - 7.0
6	SiO ₂ content on anhydrous basis	%	ISO 3262/19	98.0 Min	98.0 Min
7	Soluble Salts	%	ISO 787/13	2.0 Max	2.0 Max
8	Surface Area (BET)	m ² /gm	ASTM-D1993	180-200	180-200

* Revision Date : 01.04.2019


Revision No : 01

APPLICATIONS : MISCELLANEOUS RUBBER GOODS, FOOTWEAR ETC

PACKING & LOGISTICS	GRADE	NET WEIGHT (KG)	SHIPMENT (MT)				
			TRUCK LOAD (MT)	CONTAINER LOAD			
				UN PALLETISED		PALLETISED	
				20' FCL	40' FCL	20' FCL	40' FCL
Laminated HDPE Bags with Inner LDPE liners	MANSIL-190	25	8/13.5	7.50	17.50	5.76	16.0
	MANSIL-190G	25	9/15	9.25	21.50	6.0	19.20

Packing : Available in Paper bags, Jumbo bags & EVA bags can also be given as per customer requirement.

Testing : As per GMGB (Ref : ISO) Test Method - WI/QC/9.0/03



GUJARAT MULTI GAS BASE CHEMICALS PVT. LTD.

Opp. ONGC Colony, Palavasna, Mehsana-384003 (GUJARAT). INDIA

Tel. No. : +91 2762-225566, 225577

Fax No. : +91 2762-225544

E-mail : gujaratmulti@gmail.com Website : www.gmgsilica.com

An ISO 9001:2015, ISO 22000:2005
ISO 14001:2015, ISO 45001:2018 Certified Company
Product registered under REACH



Science in the service of Industry & Environment